



Model No. LD780A5C16 (LD-780-5A)
780nm 5mW 60°C Laser Diode in TO-18 Ø5.6mm Package

FEATURES

- 780nm 5mW CW AlGaAs Laser Diode
Low operating current
High efficiency
High operating temperature
Better power budget for optical design
Package: TO-18 (dia. 5.6mm)

APPLICATIONS

- Laser light source

ABSOLUTE MAXIMUM RATINGS

Table with 5 columns: PARAMETER, SYMBOL, CONDITION, RATING, UNIT. Rows include OPTICAL OUTPUT POWER, REVERSE VOLTAGE (LD), REVERSE VOLTAGE (PD), FORWARD CURRENT (PD), OPERATING TEMPERATURE, STORAGE TEMPERATURE.

ELECTRICAL AND OPTICAL CHARACTERISTICS (Tc = 25 °C)


Table with 7 columns: PARAMETER, SYMBOL, MIN., TYP., MAX., UNIT, CONDITIONS. Rows include LASING WAVELENGTH, THRESHOLD CURRENT, OPERATING CURRENT, DIFFERENTIAL EFFICIENCY, OPERATING VOLTAGE, MONITOR CURRENT, PARALLEL DIVERGENCE ANGLE, PERPENDICULAR DIVERGENCE ANGLE, PARALLEL FFP DEVIATION ANGLE, PERPENDICULAR FFP DEVIATION ANGLE, EMISSION POINT ACCURACY.

Note: The above specifications are subject to change without notice.





### MECHANICAL OUTLINE (unit: mm)



### PRECAUTIONS







- Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- Observing visible or invisible laser beams with human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- No laser device should be used in any application or situation where life or property is at risk in the event of device failure.
- Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.

**Note: The above specifications are subject to change without notice.**





### TYPICAL CHARACTERISTICS



Note: The above specifications are subject to change without notice.

