



DPW1940 Series 1940nm CW DPSS Laser System up to 11000mW

Overview

The DPW1940 series diode pumped solid state (DPSS) laser is ideal for applications that require a wavelength of 1940nm and output power levels up to 11000mW. The laser features a compact design, long lifetime, easy operation, and FDA-compliant system with driver. The laser is widely used in measurement, communication, spectrum analysis, and many other applications.



Specifications

Model Number	DPW1940-XYZ	
Wavelength (nm)	1940±1	
Output power (mW)	>1000 (X=1W), >3000 (X=3W), >5000 (X=5W), >8000 (X=8W), >10000 (X=10W), >11000 (X=11W)	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<10% (Z=B), <5% (Z=A), <3% (Z=E)	
Beam diameter at aperture (1/e ² , mm)	<4	
Beam divergence, full angle (mrad)	<8	
Polarization ratio	>100:1	
Warm-up time (minutes)	<10	
Beam height from base plate (mm)	93.5	
Operating temperature (°C)	15-30	
Dimensions of laser head (mm)	346(L)×140(W) ×125(H) mm ³	
Weight of laser head (kg)	5.7 kg	
Power supply options		
High Power W Version Elite Power Supply (Y=W)	Input voltage	90-264VAC
	Dimensions	307(L) ×168(W) ×123(H) mm ³
	Weight	4.5 kg
	Notes	Fixed output power
Expected lifetime (hours)	10,000	
Warranty period	10 months	
FDA Compliance	FDA CDRH Title 21 CFR 1040.10/11 Class IV	


Remarks:

- Specifications of the CW laser is based on the laser performance at full power output after the specified warmup period. The stability of output power may change when output power is adjusted at a different power level.




Outline Dimensions (unit: mm)

Laser Head



Power Supply



Note: The above specifications are subject to change without notice.