

## 808nm 200mW 50°C Laser Diode in TO-18 $\phi$ 5.6mm Package

Part No. LD808A200C15

### FEATURES

- 808nm 200mW High Power Laser Diode
- High pumping efficiency
- Stable wavelength
- High reliability
- Cost effective
- Package: TO-18 (dia. 5.6mm)

### APPLICATIONS


- Pumping source for DPSS green laser
- Medical use

### ABSOLUTE MAXIMUM RATINGS







Parameter	Symbol	Condition	Rating	Unit
Light output power	$P_O$	CW	200	mW
Reverse voltage (LD)	$V_{RL}$	-	2	V
Reverse voltage (PD)	$V_{RD}$	-	30	V
Forward current	$I_{FD}$	-	10	mA
Case temperature	$T_C$	-	-10 to +50	°C
Storage temperature	$T_S$	-	-40 to +85	°C


### ELECTRICAL AND OPTICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ )

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Peak wavelength	$\lambda$	804	-	812	nm	$P_O = 200\text{mW}$
Threshold current	$I_{th}$	-	60	100	mA	
Operating current	$I_{op}$	-	260	300	mA	
Operating voltage	$V_{op}$	-	1.9	2.2	V	
Differential efficiency	$\eta$	0.8	1.0	-	mW/mA	$P_O = 150\text{-}200\text{mW}$
Monitor current	$I_m$	0.3	-	2.4	mA	$P_O = 200\text{mW}$
Parallel divergence angle	$\Theta_{//}$	-	6	11	deg	
Perpendicular divergence angle	$\Theta_{\perp}$	-	28	40	deg	
Parallel FFP deviation angle	$\Delta \Theta_{//}$	-3	0	+3	deg	
Perpendicular FFP deviation angle	$\Delta \Theta_{\perp}$	-5	0	+5	deg	
Emission point accuracy	$\Delta x \Delta y \Delta z$	-80	0	+80	um	





## TYPICAL CHARACTERISTICS






**MECHANICAL OUTLINE (unit: mm)**



**Pin Configuration**



\*Other pin configurations may be available upon request.

**ADDITIONAL NOTES**

- Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- Observing visible or invisible laser beams with human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- No laser device should be used in any application or situation where life or property is at risk in the event of device failure.
- Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.