



PLP-L4 Series 635nm-980nm Line Generating Laser Diode Modules

With Adjustable Focus, APC Circuit Design and 4-Degree Line Generating Lens

Overview

The PLP-L4 series line generating laser diode module is designed for OEM applications with line profile and miniature size.


Features

- Wide range of wavelengths from 635nm to 980nm (including 650nm, 670nm, 780nm, 808nm, 850nm, 904nm)
- Different output power levels for different wavelengths
- Miniature design: Dia. 10.5mm x L. 20mm
- Adjustable focus
- Automatic Power Control (APC) circuit
- 4-degree line generating lens



Specifications of PLP-L4 Series Laser Diode Modules with 4-Degree Line Generating Lens

Wavelength (nm)	635	650	670	780	808	850	904	980
Laser light	Visible Red			Infrared				
Laser class	Class II <1mW, Class IIIa <5mW			Class IIIb				
Diode structure	Index guided							
Diode output power	5-10mW							
Operating current	25-50mA typical							
Operating voltage	3-6 VDC							
Drive circuit	Voltage regulated APC (automatic power control)							
Optics	Singlet plastic collimating lens plus the ~4° plastic line generating lens							
Beam size @ 1 m	~ 5.2 cm							
Beam profile	Line							
Focus	Adjustable							
Operating temperature	-10 to +40 °C or -10 to +50 °C							
Connector	Black wire -, red wire + & brass case +							
Dimensions/Weight	Dia. 10.5mm x L. 20mm; 15 gm typical							



Ordering Information

Part Number	Wavelength (nm)	Optical output power (mW)*	Laser class	Operating voltage (V DC)	Operating Current typical (mA)	Operating temperature (°C)
PLP6351AE-L4B	635	0.5-0.99	II	3-6	40	-10 to +40
PLP6353AE-L4B	635	2.1-3	IIIa	3-6	40	-10 to +40
PLP6351AE-L4A	635	0.5-0.99	II	3-6	40	-10 to +50
PLP6353AE-L4A	635	2.1-3	IIIa	3-6	40	-10 to +50
PLP6501AE-L4B	650	0.5-0.99	II	3-6	25	-10 to +40
PLP6503AE-L4B	650	2.1-3	IIIa	3-6	30	-10 to +40
PLP6501AE-L4A	650	0.5-0.99	II	3-6	25	-10 to +50
PLP6503AE-L4A	650	2.1-3	IIIa	3-6	30	-10 to +50
PLP6701AE-L4	670	0.5-0.99	II	3-6	40	-10 to +50
PLP6703AE-L4	670	2.1-3	IIIa	3-6	40	-10 to +50
PLP7803AE-L4	780	2.1-3	IIIb	3-6	30	-10 to +50
PLP8083AE-L4	808	2.1-3	IIIb	3-6	30	-10 to +50
PLP8503AE-L4	850	2.1-3	IIIb	3-6	30	-10 to +50
PLP9043AE-L4	904	2.1-3	IIIb	3-6	30	-10 to +50
PLP9806AE-L4	980	4.2-6	IIIb	3-6	45	-10 to +50

Additional Notes

- The PLP-L4 series laser modules are designated solely as OEM components for incorporation into the customer's end products. Therefore, it is the customer's responsibility to comply with the appropriate requirements of FDA 21CFR, section 1040.10 and 1040.11 for complete laser products. For the code of FDA regulations, please refer to [FDA Performance Standards for Light-Emitting Products](#) for detailed information.
- Additional heat sink may be needed if the laser module is operated continuously for a long period of time.
- Specifications are subject to change without notice.