




808nm 7000mW VCSEL Diode in 7471 Package

Part No. VC74A-808H7WA

Features

- 7471 package, Substrate AlN
- Low wavelength drift
- High reliability and easy to collimate
- Low threshold current
- Small emission area
- Number of emitters: 1184
- 7W 808nm VCSEL @ 8.46A



7471 Package

Applications

- Lidars
- IR illumination
- 3D sensor
- Solid-state pump source
- Medical application

Specifications

Absolute Maximum Ratings				
Parameters	Symbol	Rating	Unit	Conditions
Case Operating Temperature	Top	-40 to 85	°C	
Storage Temperature	Tstg	-40 to 105	°C	
Reflow Soldering Temperature	Tsol	260°C	°C	10 seconds
Reverse Voltage	Vr	5	V	
Maximum Continuous Current	I _{max}	15	A	
ESD Exposure (Human Body) Model	ESD	2K	V	

Notes:

- Stresses greater than those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or other conditions above those indicated in the operations section for expanded periods of time may affect reliability.
- In its maximum rating diode laser operation could damage its performance or cause potential safety hazard such as equipment failure.
- Electrostatic discharge is the main reason for laser fault of the diode. Take effective precautions against ESD. When dealing with laser diodes, use wrist strap, grounding work surface and strict antistatic technology.


Electro-Optical Characteristics (T _{op} =25°C, CW mode)						
Parameters	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold Current	I _{th}	-	1.8	-	A	
Forward Current	I _F	-	8.46	-	A	
Optical Output Power	P _o	-	7	-	W	I _F =8.46A
Forward Voltage	V _f	-	2.34	-	V	I _F =8.46A
Power Conversion Efficiency	PCE	-	35	-	%	I _F =8.46A
Slope Efficiency	η	-	0.84	-	W/A	I _F =8.46A
Series Resistance	R	-	0.08	-	Ohm	I _F =8.46A
Peak Wavelength	λ _P	800	808	816	nm	P _o =7W
Spectral Width	FWHM _s	-	2	-	nm	I _F =8.46A
Wavelength Temperature Drift	Δλ _P / ΔT	-	0.07	-	nm/°C	I _F =8.46A
Beam Divergence	FWHM _B	-	20	-	Deg	
Emission Area			1179 x 1147		um ²	
No. of Emission Aperture			1184			

Note: Electro-optical characteristic with a package or diffuser would require further evaluation. Values are based on limited sample size and estimated values.




Typical Characteristics


LIV Graph




Intensity vs. Wavelength




Outline Dimensions (unit: mm)





SMT Reflow Soldering Curve



Note: Reflow soldering can be operated only one time. During the temperature ramp-up, no forces may be exerted on the LD which would deform or damage them. After soldering is completed, please do not process until the product temperature ramps down to room temperature.

Additional Notes

1. Please use solder paste to cure the laser diode.
2. Please make sure that the heat of VCSEL diode has been completely conducted to metal shell to avoid affecting the optical power output.
3. This VCSEL diode can be only used in constant voltage and current.
4. Please do not aim the laser at people or animals.
5. You may observe the laser spot through an image monitoring equipment.
6. Please do not touch VCSEL diode surface by naked hands or squeeze the sealant on VCSEL diode surface. It may cause wrong optical angle and distorted laser spot, and even damage the VCSEL diode.
7. Please use ceramic suction nozzle to absorb the VCSEL diode, so as to avoid VCSEL diode sticking to the nozzle.
8. Please add a 0.02s blowing action after locating the laser diode to aluminum substrate.
9. Specifications are subject to change without notice.